Permit #

## COMMERCIAL DRIVEWAY PERMIT APPLICATION

Schedule inspection by 3:00 p.m. day prior (303) 621-3160 Driveway Permits are Valid for 1 (one) Year from Date of Purchase

Check#	Date Paid			Permit Fee	\$105.00
Property Owner _		Phone		Fax	
Mailing Address _	Street / PO Box				
Address of Propert	Street / PO Box  y		City	State	Zip
<ul> <li>If not staked and r</li> <li>The final driveway</li> <li>A site plan must b</li> <li>This is an applicate</li> <li>Standard specificate</li> <li>All failed inspection</li> <li>Applicant understapplicant/owner examplicant shall be</li> </ul>	clearly marked and staked within 24 marked, a \$47.00 re-inspection fee by inspection must be scheduled not be attached that clearly shows where the close are provided as an example ons will be assessed a prepaid \$47. ands that driveway must be maintated as a prepaid \$47. The consistency must be maintated by County does not grant legal actions.	will be assessed. less than 14 days before e the driveway is to be lo oes not constitute approv- other requirements may 00 re-inspection fee. ined to County specificator r legal right for driveway	cated. val. apply. tions at all times.	Any future repairs s	hall be at
Date Issued:	Month	Day	Ye	ear	
Expiration Date	Month	Day	Ye	ear	
		X	PPLICANT SIC	GNATURE	
	Ins	spector Section			
Initial Inspection  Comments	Approved/Date		pproved/Date		
Inspected By:					
	Approved/Date				
	de: YesNo			No	

## **DRIVEWAY REQUIREMENTS**

40' turning radius at County road/private road	
Width (32' minimum) from property line to edge of county road/private road	
Gravel depth (6") on natural drives and over culverts	
Class VI gravel minimum	
Gravel from property line to shoulder of county road/private road	
Culvert diameter	
Culvert length (44') + flared ends	
All driveways that meet or join paved roads must be paved with asphalt	
Depth or thickness of pavement (4' min)	
Drive must be paved from the property line to the edge of the paved portion of the county/private	
Concrete pan 9'x20' overall dimensions	
Wire mesh or rebar	
Footers required 2'x 3'x 6"	
Adequate sight distance per County code	
Drive must have a 1% fallback measured from the centerline ditch to the property line	
It is recommended that a 20' minimum width be maintained for the entire length of the driveway for health, safety and welfare reasons.	
INSPECTOR FINAL REPORT:	